

Adapter/ Kabel	Connector 1	Connector 2	Length (inch)	Freq. (GHz)	VSWR	Invent. 10.04.	List Price (€)	Discount (%)	Easter Egg Price (€)
Alle Preise solange Vorrat reicht, Zwischenverkauf vorbehalten. Die Preise verstehen sich EXW Sindelfingen zuzügl. MwSt.									

Maury microwave Color Connect Precision Adapters



CC-A-185-FF	1.85 female	1.85 female	-	65	<=1.2	1	453	13%	395,00
CC-A-185-MF	1.85 male	1.85 female		65	<=1.2	2	453	13%	395,00
CC-A-185-MM	1.85 male	1.85 male		65	<=1.2	3	453	13%	395,00
CC-A-24292-FF	2.4 female	2.92 female		40	<=1.14	6	336	12%	295,00
CC-A-24292-FM	2.4 female	2.92 male		40	<=1.14	3	336	12%	295,00
CC-A-24292-MM	2.4 male	2.92 male		40	<=1.14	12	336	12%	295,00
CC-A-24-MF	2.4 male	2.4 female		50	<=1.17	2	336	12%	295,00
CC-A-24-MM	2.4 male	2.4 male		50	<=1.17	4	336	12%	295,00

Maury microwave Test Essentials Lab Adapters



TE-A-185-FF	1.85 female	1.85 female		65	<=1.3	2	227	14%	195,00
TE-A-2435-FF	2.4 female	3.5 female		26.5	<=1.15	4	209	7%	195,00
TE-A-2435-FM	2.4 female	3.5 male		26.5	<=1.15	2	209	7%	195,00
TE-A-35-MM	3.5 male	3.5 male		26.5	<=1.2	1	134	29%	95,00
TE-A-35N-FF	3.5 female	N female		18	<=1.15	3	111	14%	95,00
TE-A-35N-FM	3.5 female	N male		18	<=1.15	9	111	14%	95,00
TE-A-35N-MF	3.5 male	N female		18	<=1.15	3	111	14%	95,00
TE-A-35N-MM	3.5 male	N male		18	<=1.15	4	111	14%	95,00
TE-A-SMA-FF	SMA female	SMA female		18	<=1.15	5	23	16%	19,50
TE-A-SMA-MF	SMA male	SMA female		18	<=1.15	2	23	16%	19,50
TE-A-SMA-MM	SMA male	SMA male		18	<=1.15	22	23	16%	19,50
TE-A-SMAN-MF	SMA male	N female		18	<=1.15	3	87	14%	75,00

Maury microwave Stability Cable Assemblies



SC-24-MM-48	2.4 male	2.4 male	48	50	<=1.43	6	2.000	5%	1.895,00
SC-292-MM-24	2.92 male	2.92 male	24	40	<=1.40	5	643	8%	595,00
SC-292-MM-36	2.92 male	2.92 male	36	40	<=1.40	4	679	12%	595,00
SC-292-MM-60	2.92 male	2.92 male	60	40	<=1.40	1	750	7%	695,00
SC-292-MM-78	2.92 male	2.92 male	78	40	<=1.40	1	806	14%	695,00
SC-35-MM-24	3.5 male	3.5 male	24	26.5	<=1.35	1	565	12%	495,00
SC-35-MM-60	3.5 male	3.5 male	60	26.5	<=1.35	2	671	11%	595,00
SC-35-MM-78	3.5 male	3.5 male	78	26.5	<=1.35	2	753	8%	695,00
SC-N-MM-24	N male	N male	24	18	<=1.30	2	565	12%	495,00
SC-N-MM-36	N male	N male	36	18	<=1.30	2	600	18%	495,00
SC-N-MM-60	N male	N male	60	18	<=1.30	2	671	11%	595,00
SC-N-MM-78	N male	N male	78	18	<=1.30	2	727	18%	595,00

Maury microwave Utility Cable Assemblies



UC-SMA-MM-24	SMA male	SMA male	24	20	<=1.25	5	190	21%	149,50
UC-SMA-MM-36	SMA male	SMA male	36	20	<=1.25	8	202	4%	195,00
UC-SMA-MM-48	SMA male	SMA male	48	20	<=1.25	9	214	9%	195,00
UC-SMA-MM-60	SMA male	SMA male	60	20	<=1.25	3	226	14%	195,00
UC-SMA-MM-78	SMA male	SMA male	78	20	<=1.25	2	250	22%	195,00

Adapter/ Kabel	Connector 1	Connector 2	Length (inch)	Freq. (GHz)	VSWR	Invent. 10.04.	List Price (€)	Discount (%)	Easter Egg Price (€)
Alle Preise solange Vorrat reicht, Zwischenverkauf vorbehalten. Die Preise verstehen sich EXW Sindelfingen zuzügl. MwSt.									

bsw Quality Proven Products



Torque Wrench TW-8-057NM-N2	3.5, 2.92, 2.4, 1.85	setting 8lb-in, 0.90Nm (gold)				9	120	21%	95,00
Torque Wrench TW-8-090NM-N2	SMA	setting 5lb-in, 057Nm (blue)				16	95	0%	95,00
Silver Line SRCONF-141SMAMM-03.0	hand-conformable	SMA male-male	3	18		5	17	13%	14,95
Silver Line SRCONF-141SMAMM-04.0	hand-conformable	SMA male-male	4	18		37	17	13%	14,95
Silver Line SRCONF-141SMAMM-05.0	hand-conformable	SMA male-male	5	18		36	17	13%	14,95
Silver Line SRCONF-141SMAMM-06.0	hand-conformable	SMA male-male	6	18		40	19	14%	15,95
Silver Line SRCONF-141SMAMM-07.0	hand-conformable	SMA male-male	7	18		34	19	14%	15,95
Silver Line SRCONF-141SMAMM-08.0	hand-conformable	SMA male-male	8	18		29	19	14%	15,95
Silver Line SRCONF-141SMAMM-09.0	hand-conformable	SMA male-male	9	18		8	19	14%	15,95
Silver Line SRCONF-141SMAMM-10.0	hand-conformable	SMA male-male	10	18		47	19	14%	15,95
Silver Line SRCONF-141SMAMM-11.0	hand-conformable	SMA male-male	11	18		47	20	14%	16,95
Silver Line SRCONF-141SMAMM-12.0	hand-conformable	SMA male-male	12	18		60	20	14%	16,95
Silver Line SRCONF-141SMAMM-13.0	hand-conformable	SMA male-male	13	18		45	20	14%	16,95
Silver Line SRCONF-141SMAMM-14.0	hand-conformable	SMA male-male	14	18		50	20	14%	16,95
Silver Line SRCONF-141SMAMM-15.0	hand-conformable	SMA male-male	15	18		53	20	14%	16,95
Silver Line SRCONF-141SMAMM-16.0	hand-conformable	SMA male-male	16	18		31	20	14%	16,95
Silver Line SRCONF-141SMAMM-17.0	hand-conformable	SMA male-male	17	18		35	20	14%	16,95
Silver Line SRCONF-141SMAMM-18.0	hand-conformable	SMA male-male	18	18		46	20	14%	16,95
Silver Line SRCONF-141SMAMM-20.0	hand-conformable	SMA male-male	20	18		36	20	14%	16,95
Silver Line SRCONF-141SMAMM-22.0	hand-conformable	SMA male-male	22	18		36	20	14%	16,95
Silver Line SRCONF-141SMAMM-24.0	hand-conformable	SMA male-male	24	18		39	21	14%	17,95
Silver Line SRCONF-141SMAMM-25.0	hand-conformable	SMA male-male	25	18		27	21	14%	17,95
Silver Line SRCONF-141SMAMM-28.0	hand-conformable	SMA male-male	28	18		27	21	14%	17,95
Silver Line SRCONF-141SMAMM-32.0	hand-conformable	SMA male-male	32	18		28	22	14%	18,95
Silver Line SRCONF-141SMAMM-36.0	hand-conformable	SMA male-male	36	18		24	22	14%	18,95
Silver Line SRCONF-141SMAMM-48.0	hand-conformable	SMA male-male	48	18		25	25	19%	19,95
Blue Line BL-SMA18-MM-06	flexible	SMA male-male	6	18		30	48	18%	39,50
Blue Line BL-SMA18-MM-12	flexible	SMA male-male	12	18		29	50	20%	39,50
Blue Line BL-SMA18-MM-18	flexible	SMA male-male	18	18		29	51	23%	39,50
Blue Line BL-SMA18-MM-24	flexible	SMA male-male	24	18		39	53	25%	39,50
Blue Line BL-SMA18-MM-36	flexible	SMA male-male	36	18		42	55	10%	49,50
Blue Line BL-SMA18-MM-48	flexible	SMA male-male	48	18		29	57	13%	49,50
Blue Line BL-SMA18-MM-60	flexible	SMA male-male	60	18		28	59	16%	49,50
Blue Line BL-SMA18-MM-72	flexible	SMA male-male	72	18		29	60	18%	49,50
Blue Line BL-SMA18-MM-84	flexible	SMA male-male	84	18		28	62	20%	49,50