

PROBE SYSTEM FOR LIFE



DATA SHEET

M6 – 150 mm Manual Probe System

The SemiProbe M6 is the most modular and flexible 150 mm manual probe system available today. It is built using our patented Probe System for Life (PS4L) architecture which provides unsurpassed flexibility and significant capital equipment savings. With the PS4L, customers can purchase a manual 150 mm system that meets their precise specifications and requirements.

The Probe System for Life (PS4L) family of wafer probing systems is designed based on SemiProbe's patented adaptive architecture. Unlike traditional probe systems, all foundation modules – bases, stages, chucks, microscope mounts, microscope movements, optics, manipulators and more – are interchangeable, making the PS4L the consummate solution for many different applications and budgets. This unique modular design enables customers to acquire test capabilities that precisely match their requirements. More important, as the environment or test conditions change, the PS4L can easily be field-upgraded to meet these new demands. With this design philosophy, PS4L customers realize substantial time and cost savings over traditional probe systems because they do not need to invest in a new platform when wafer size, levels of automation or test requirements change.



A complete line of accessories is available for the M6 system including probe card holders, manipulators, manipulator arms & bases, probe tips, lasers, optics, CCTV systems, vibration isolation tables, dark boxes and much more.

FEATURES AND BENEFITS

- 150 mm manual system with upgrade path to 200 mm manual system
- 150 mm manual system with upgrade path to 150/200 mm semiautomatic system
- All key components are interchangeable which enables the system to easily be configured to meet applications and budgets – present and future
- Software and hardware modules provide a perpetual field upgrade path

Major Applications/Markets Served

Device Characterization, MEMS, Optoelectronics, HF/Microwave, Photovoltaic, Failure Analysis, Research, Material Science and more

SPECIFICATIONS

Dimensions	750 mm x 650 mm x 750 mm (29.5" x 25.4" x 29.5") (W,H,L) - with optics
Weight	70 Kg (155 lbs.)
Chuck Stage X-Y Movement	Several stages to select from to meet performance and budget requirements Travel: 155 mm x 155 mm Planarity: +/- 10 µm over travel range Resolution: 5 µm Independent X and Y linear movement
Chuck Stage Z Movement	Z Travel: 10 mm Z Contact/Separation Stroke: 4 mm adjustable
Theta Movement	Travel: 360 degrees
Chucks	Vacuum or mechanical clamping, round or square, ambient, thermal and custom Handle die, wafer packs, sawn wafers on frame, broken wafers and full wafers up to 150 mm Nickel plated steel with concentric vacuum rings (standard), other plating materials available Planarity: 10 µm
Platen:	Aluminum with stainless steel top 360 degree manipulator placement Manipulator fixation - magnetic, vacuum
Platen Movement	Platen Lift: Choice of fixed or adjustable Adjustable: Coarse - 25 mm, Fine - 6 mm
Microscope Mounting/Movement	Mounting - Boom, Post or Bridge Movement - Manual or Programmable - 50 x 50 mm, 50 x 75 mm, 100 x 100 mm
Optics	Stereo Zoom, Zoom Tube, A-Zoom or Compound Microscope
Utilities	Power: AC 110/220V AC 50-60 Hz 20A Vacuum: 23 Hg or -0.8 bar

Note: Data and specifications vary depending on probe system configurations and accessories

PHYSICAL DIMENSIONS

